

## Hypac 50 Hz Enclosed - Refrigerant Dryer Range



Model		Mounting Config	Voltage/Phase	Starter Type	Motor Speed (rpm)	Receiver Capacity (litres)	Air Outlet (Rp)	Package Dimensions (mm)			Ambient Temp Min - Max (°C)	Pressure Dew Point (°C)	Air Quality (mg/m <sup>3</sup> )
								Depth	Width	Height			
HV11 HV11RS	ACER	Receiver	400V 3Ph	SD	1450	272	¾"	1187	1355	1550	0-40	8	<2
	ACED	Dryer				-		825	1215			3	<1
	AERD	Dryer + Receiver				272		1187	1355			8	<2
HV15 HV15RS	ACER	Receiver				-		825	1215			3	<1
	ACED	Dryer				272		1187	1355			8	<2
	AERD	Dryer + Receiver				-		825	1215			3	<1
HV18 HV18RS	ACER	Receiver				272		1187	1355			8	<2
	ACED	Dryer				-		825	1215			3	<1
	AERD	Dryer + Receiver				272		1187	1355			8	<2
HV22 HV22RS	ACER	Receiver				-		825	1215			3	<1
	ACED	Dryer				272		1187	1355			8	<2
	AERD	Dryer + Receiver				-		825	1215			3	<1