

Enclosed - Fixed Speed



Note: The 50 Hz / 400 Volts / 3 Phase Regulated Speed (RS) models also cover 60 Hz / 460 Volts / 3 Phase

Motor Power (kW)	Model	50Hz		60Hz		Mount Config.	Maximum FAD m ³ /min (cfm)				Motor Speed (rpm)		Oil Cap. (litres)	Air Outlet (Rp)	Dimensions (mm)			Noise dB(A)	Weight (kg)	Air Quality (mg/m ³)			
		Voltage/Phase	Starter Type	Voltage/Phase	Starter Type		50Hz		60Hz		50Hz	60Hz			Depth	Width	Height						
							8 bar	10 bar	8 bar	10 bar													
11.0	HV11	400V 3Ph	SD	460V 3Ph	DOL	Floor	1.63 (57.6)	1.41 (49.8)	1.48 (52.4)	1.29 (45.6)	1450	1760	7.0	¾"	850	700	1550	69	384	<3			
15.0	HV15						2.21 (78.1)	2.01 (71.0)	1.90 (67.1)	1.65 (58.4)								70	397				
18.0	HV18						2.88 (101.7)	2.55 (90.1)	2.80 (99.0)	2.44 (86.2)								7.5	1"		70	481	
22.0	HV22						3.60 (127.1)	2.96 (104.5)	3.25 (114.6)	2.83 (100.0)			7.5	1"				71	494				
30.0	HV30						5.00 (176.6)	4.31 (152.2)	4.43 (156.5)	3.86 (136.2)			23.0	1½"				1130	900		1640	73	857
37.0	HV37						5.95 (210.1)	5.07 (179.0)	5.48 (193.7)	4.77 (168.5)													911
45.0	HV45						7.33 (258.9)	6.54 (231.0)	6.54 (231.0)	5.73 (202.3)													940
75.0	HV75	400V 3Ph	Star Delta	-	-	Floor	12.06 (425.9) @ 7.5 bar		-	1450	-	1.0	1½"	955	2330	1600	73	1450	<3				