

Technical Specifications

L160 - L250RS

MODEL*	Drive Motor kW	Free Air Delivered (m ³ /min)**			Dimensions (mm)			Noise level*** dB (A)	Weight kg
		7.5 bar g	10 bar g	13 bar g	Length	Width	Height		
L160	160	28.4	25.1	21.3	2800	1920	2073	76	4060
L200	200	36.6	31.0	27.2	2800	1920	2073	78	4500
L250	250	42.7	38.0	33.2	2800	1920	2073	78	5030
L160 RS	160	9.88 - 27.55	9.78 - 24.35	8.60 - 20.70	3579	1920	2073	81	4900
L200 RS	200	9.64 - 35.50	9.74 - 30.07	9.20 - 26.40	3579	1920	2073	82	5400
L250 RS	250	10.30 - 41.40	10.12 - 36.86	9.95 - 32.32	3579	1920	2073	82	5550

* Water cooled models available

** Data measured and stated in accordance with ISO 1217 Ed. 4, Annex C & Annex E and Pneurop/Cagi PN2CPTC2 and the following conditions:
Air Intake Pressure 1 bar a
Air Intake Temperature 20 °C
Humidity 0 % (Dry)

*** Measured in free field conditions in accordance with the Pneurop / Cagi PN8TNC2.2 test code, + / - 3 dB

CompAir policy is one of continuous improvement and we therefore reserve the right to alter specifications and prices without prior notice. All products are sold subject to the Company's conditions of sale.